

## CV 320 Asphalt Remover Gel

### CLASSIFICATION:

- Ready to use thickened asphalt remover

### PACKAGING:

Jug	Pail	Drum
4L	20L	210L

### DESCRIPTION:

- Powerful ready to use product formulated for the removal of asphalt, tar, hardened grease, grime and oils.
- Viscous product for application from a pump up sprayer. Provides vertical cling for increased, efficient contact time. Ideal for use on vertical surfaces.
- May be safely used on asphalt pavers, machinery, tools, engines.
- Freely rinses with water.

### CHEMICAL AND PHYSICAL PROPERTIES:

- Appearance Translucent viscous liquid
- Odour Citrus
- pH 8.0 – 9.5
- Specific Gravity 0.9
- Viscosity 200 - 500 cps

### USE DIRECTIONS:

- **Dilution:** Use in undiluted form.
- **Cleaning Asphalt Pavers, Equipment, Tools:**
  - ❖ Apply RTU gel with a pump up sprayer.
  - ❖ Allow a minimum 15 minute contact time, longer for heavier asphalt build-ups.
  - ❖ Do not allow surface to dry.
  - ❖ Scrub or scrape as necessary.
  - ❖ Rinse with water.

*See Material Safety Data Sheet for proper handling and safety instructions.*